

Last updated: 25/06/2024 17:10:48

# NITROGEN N-5030 FILLING

Product group: **714**    Product number: **905208**

Nitrogen 3.0 grade is predominantly used for purging. This product is delivered in a Unitor cylinder as part of WSS global cylinder exchange program.



## Product information

Nitrogen in 3.0 Grade has 99.9% purity. This product is delivered in a 50 litre cylinder. Product does not come with a certificate to confirm its purity. An inert gas, it is normally used for purging and blanketing applications. Beware of asphyxiation hazards when using the gas.

### Features

- Nitrogen is a colourless, odourless and tasteless
- Non-combustible and non-toxic
- Slightly lighter than air and it's an inert gas
- Nitrogen is well suited for purging or flushing cargo tanks and pipelines of residual gases and vapours prior to loading cargo or doing maintenance
- It is also used as a 'blanket' on top of several types of cargoes to prevent reactions with oxygen from atmospheric air.
- The filling pressure is lower in some locations than the normal 200 bar due to local rules and regulations that limit filling pressure.
- Nitrogen 3.0 means > 99.9% pure and the impurities: Water (H2O) < 1000 ppm and Oxygen (O2) < 1000 ppm.

### Benefits

- Perfectly suited for purging, inerting / blanketing
- For your safety, the product is delivered in a Unitor exchange cylinder complete with barcode and unique cylinder serial number
- We trace and track all cylinders using our system to give you peace of mind
- We offer global availability through our Global Exchange Programme.

## Specification

### General

<b>Cylinder Type</b>	N-50
<b>Invent Hazard Material (IMO/EU) classification</b>	NA

### Physical properties

<b>Colour</b>	green
---------------	-------

### Dimensions/Weight

<b>Connection [Size/ Type]</b>	W24.32mm x 1/14" RH Ext
<b>Diameter [mm]</b>	230
<b>Gross Weight [kg]</b>	92
<b>Height [mm]</b>	1690
<b>Weight [kg]</b>	11.5 Net

### Technical data

<b>Connection [inch]</b>	W24.32mm x 1/14" RH Ext
<b>Filling pressure [bar]</b>	up to 200bar
<b>Purity</b>	3.0 > 99.9%
<b>Volume (l)</b>	50

### Performance data

<b>Gas Capacity [m³]</b>	10.2
--------------------------	------

## Documents

[Nitrogen](#)

[SDoC and MD for IHM](#)

## Related products

### Accessories

**550160**  
WASHER ALU 10 PCS FOR OX REGULATOR

**510002**  
REGULATOR 510 N2 PRESSURE 0-10 BAR

**771713**  
REGULATOR 600 NITROGEN 0-200 BAR

**510011**  
REGULATOR 510 N2 FLOW0-1.3 L/MIN

**778147**  
TROLLEY F/1 40-50L GAS CYLINDER

Is frequently bought together with

**905607**  
UNICOOL R-407C 52 KG REFRIGERANT

**571356**  
ROCOR NB LIQUID 25 LTR

**698720**  
AUTOTREAT - 25 LTR

**905026**  
ACETYLENE A-40 FILLING

**905034**  
OXYGEN O-40 FILLING

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/gases/nitrogen/nitrogen-n-5030-filling/>