

Last updated: 16/02/2024 06:10:05

# UNICOOL R-410A 45 KG REFRIGERANT

Product group: **594** Product number: **905608**

A synthetic HFC refrigerant which is harmless to the ozone layer. The gas is used in a variety of maritime refrigeration applications such as low, medium and high temperature applications (evaporating temperatures of -45 to +8° C).



## Product information

### Features

- All refillable cylinders are inspected prior to refilling
- Residue refrigerant recovered to prevent environmental damage
- Content is 100% genuine refrigerant from approved producer
- Conforms to AHRI-700 purity standard
- For new systems only

### Benefits

- Worldwide compliance
- Assured quality
- Refillable cylinders

## Specification

### General

Cylinder Type	Refr-56
GWP	2090
Invent Hazard Material (IMO/IU) classification	C-25
ODP	0

### Physical properties

Colour	Light Pink
--------	------------

### Dimensions/Weight

Connection [Size/ Type]	CGA660
Diameter [mm]	254
Gross Weight [kg]	74 approx.
Height [mm]	1380
Weight [kg]	45 Net

### Technical data

ODP = Ozone Depletion Potential

GWP = Global Warming Potential (IPCC Fourth Assessment Report - AR4)

## Documents

[SDoC and MD for IHM](#)

## Related products

### Accessories

**597757**  
CHARGING HOSE SET UCH-72 3X1.8M

**544932**  
REFRIGERANT CYL. VALVE ADAPTOR SET

**513564**  
CYLINDER STAND

Is frequently bought together with

**905208**

NITROGEN N-5030 FILLING

**716142**

REFRIGERANT LEAK DETECTOR UNIRX-1A

**752154**

REFRIGERATION HANDY TOOLS CASE

**652522**

REFRIGERANT RECOVERY PACKAGE F/220V

**743466**

DUCT AIR TREATMENT 2KG

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/refrigerants/r-410a/unicool-r-410a-45-kg-refrigerant>