

Last updated: 15/02/2023 05:24:14

MINIMIX 34 4-MIX 50 CO 25 H2S 50LEL CH4 18 OX

Product group: **718** Product number: **741306**

Span gases are used for calibration and bump testing of gas detection equipment. Currently two types of disposable cylinders are in use depending on the gas mixture: - Minimix 34 is an aluminium disposable cylinder with 34 litres of gas - Minimix 58 is an aluminium disposable cylinder with 58 litres of gas



Product information

This product supersedes product no: **710087**

Gas Composition:

Methane (CH4) - 2.5% (50% LEL)
 Oxygen (O2) - 18%
 Hydrogen Sulfide (H2S) - 25ppm
 Carbon Monoxide (CO) - 50ppm
 Nitrogen (N2) - balance

Used with regulator 620013

Features

- Lightweight and disposable cylinder
- Compact size
- Comes standard with CGA C-10 connection
- Each cylinder delivered with a Certificate of Analysis
- Guaranteed and repeatable quality

Benefits

- Safe handling of gas
- Portable and easy to carry around
- Easy stock control
- Single regulator type needed across
- Compliant to vetting inspection requirements

Specification

General

Cylinder Type	Mnimix 34
Invent Hazard Material (IMO/EU) classification	NA

Dimensions/Weight

Connection [Size/ Type]	CGA C-10
Diameter [mm]	76
Height [mm]	289

Technical data

Shelf life [months]	24
Volume (l)	0.9

Documents

[SDoC and MD for IHM](#)

[Span-Gases](#)

Related products

Accessories

620013
 REGULATOR F/SCOTTY M AND 4COMP

Is frequently bought together with

905034

OXYGEN O-40 FILLING

905026

ACETYLENE A-40 FILLING

905606

UNICOOL R-404A 45 KG REFRIGERANT

620138

MINIMX 58 HYDROGEN SULPHIDE(H₂S) 25 PPM IN NITROGEN

778175

MINIMX 34 4-MX 50 CO 25 H₂S 50LEL CH₄ 12 OX

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/spangases/disposables/4-mix-50-co-25-h2s-50lel-ch4-18-ox/>