

Last updated: 16/02/2023 08:45:35

MINIMIX 58 HYDROGEN SULPHIDE(H₂S) 25 PPM IN NITROGEN

Product group: **718** Product number: **620138**

Span gases are used for calibration and bump testing of gas detection equipment. Currently two types of disposable cylinders are in use depending on the gas mixture: - Minimix 34 is an aluminium disposable cylinder with 34 litres of gas - Minimix 58 is an aluminium disposable cylinder with 58 litres of gas



Product information

This product supersedes product no: **L38348**

Gas Composition:

Hydrogen Sulfide (H₂S) - 25ppm

Nitrogen (N₂) - balance

Used with regulator 620013

Features

- Lightweight and disposable cylinder
- Compact size
- Comes standard with CGA C-10 connection
- Each cylinder delivered with a Certificate of Analysis
- Guaranteed and repeatable quality

Benefits

- Safe handling of gas
- Portable and easy to carry around
- Easy stock control
- Single regulator type needed across
- Compliant to vetting inspection requirements

Specification

General

Cylinder Type	Mnimix 58
Invent Hazard Material (IMO/EU) classification	NA

Dimensions/Weight

Connection [Size/ Type]	CGA C-10
Diameter [mm]	89
Height [mm]	343

Technical data

Shelf life [months]	24
Volume (l)	1.7

Documents

[SDoC and MD for IHM](#)

[Span-Gases](#)

Related products

Accessories

620013
 REGULATOR F/SCOTTY V AND 4COMP

Is frequently bought together with

620039

MNIMX17 CARBON MONOXIDE 60PPM

619965

MNIMX17 2.5% METHANE-AIR

778175

MNIMX34 4-MX50 CO 25 H2S 50LEL CH4 12 OX

619973

MNIMXPURE NITROGEN

619932

MNIMX17 ISOBUTANE 0.9%AIR

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/spangases/disposables/hydrogen-sulphiden2-25-ppm-s-58/>