Last updated: 20/02/2023 05:35:19

# O2 1.5% IN N2 98.5% SG-10 FILLING

Product group: 718 Product number: 778176

Span gases are used for calibration and bump testing of gas detection equipment.

# **Product information**

Gas Composition:

Oxygen (O2) - 1.5% Nitrogen (N2) - balance

# Paired with regulator 510011

#### Features

- Delivered in a refillable SG10 cylinder
- Small cylinder size makes it portable for bumptesting / calibration
- · Each cylinder comes with a Certificate to confirm its contents

## Benefits

- For your safety, the product is delivered in a Unitor exchange cylinder complete with barcode and unique cylinder serial number.
- We trace and track all cylinders using our system to give you peace of mind.
- We offer global availability through our Global Exchange Programme.

# **Specification**

# General

Cylinder Type	SG-10
Invent Hazard Material (IMO/EU) classification	NA

Dimensions/Weight

Connection [Size/ Type]	W24.32mmx 1/4" Ext.
Diameter [mm]	140
Gross Weight [kg]	21
Length	1000

### Technical data

Shelf life [months]	36
Volume (I)	10

# **Documents**

SDoC and MD for IHM

Span-Gases

# **Related products**

Accessories 510011 REGULATOR 510 N2 FLOW 0-1.3 L/MIN

Is frequently bought together with REGULATOR 510 N2 FLOW 0-1.3 L/MIN 905601 NITROGEN N-5050 FILLING

905034 OXYGEN O-40 FILLING 905026 ACETYLENE A-40 FILLING 510011



905602 NITROGEN N-1050 FILLING

This page is printed from

https://www.wilhelmsen.com/product-catalogue/products/gases-refrigerants-and-cylinders/spangases/nitrogen-mixtures/o2-1.5-in-n2-98.5/interval and interval and