

Last updated: 20/12/2023 02:03:45

UNITOR CLEANRIG CHP 1000 LTR

Product group: **641** Product number: **726015**

Unitor[™] Cleanrig CHP[™] is a water-based rig cleaner specially designed to provide efficient cleaning and optimum environmental and handling properties.

Product information

This product supersedes product no: **L724617**

Unitor[™] Cleanrig CHP[™] contains unique environmentally adapted surfactants, pH regulating additives and corrosion inhibitors allowing removal of oil spills, sludge, oil- and water based mud, dirt and grime from all surfaces included painted.

Features

- Water based cleaner
- Rig cleaner for use on deck, tanks, engine rooms, drilling equipment
- Biodegradable
- Non-toxic and Non-flammable
- No hydrocarbon solvents
- Contains no nonyl phenol ethoxylates or other estrogenic compounds

Benefits

- High efficient cleaning
- Can be used in confined rooms
- Removes oil spills, sludge, mud, dirt and grime
- Leaves a good shine on hard surfaces after cleaning

This bundle contains:

726040
UNITOR CLEANRIG CHP 200 LTR

Specification

General

Invent Hazard Material (IMO/IU) classification	NA
--	----

Physical properties

Appearance	Pale yellow
Density [g/ml]	1,08 - 1,09
Form	Liquid
pH	12-13

Technical data

Compatibility	The concentrated product may react with aluminium, zinc, tin and their alloys. May swell natural or synthetic rubber
---------------	--

Approvals

Unitor[™] Cleanrig CHP[™] is HOCNF and CEFAS approved. According to Norwegian environmental authorities Unitor[™] Cleanrig CHP[™] is classified as "Yellow" product containing biodegradable surfactants and pH-regulating compounds.

Documents

[Cleanrig CHP CEFAS Certificate 2022](#)

[SDoC and MD for IHM](#)

Directions for use

Unitor[™] Cleanrig CHP[™] is an alkaline cleaner designed to remove oil and grease by penetration of surfactants creating an emulsion, which is washed away with water. PH regulating additives provide increased action and dissolution of hydrocarbons and dirt particles.

Dosage: 1:1 - 1:50

Dosing is depending on the amount and type of soil to be removed, but often low concentrations are sufficient. Uitor™ Cleanrig CHP™ is applied by spraying or by other means on to surfaces that requires cleaning. Allow the cleaning solution to penetrate soil for 10-30 minutes depending on amount and type of soil as well as the temperature. During this time the cleaning solution should not be allowed to dry on the surface to be cleaned. Wash down with water hose preferably with hot water or by use of high pressure cleaning equipment.

Related products

Is frequently bought together with

777710

NALFLEET 2000 25 LTR

661843

DEFOAMER CONCENTR. 25 LTR

571679

METAL BRITE HD 25 LTR

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/cleaning-chemicals/hocnf--cef-as-offshore-chemicals/unitor-cleanrig-chp-1000-ltr>