

Last updated: 30/04/2025 05:20:36

# DIESELPower BIO ENHANCER 25 LTR

Product group: **650**      Product number: **767340**

Unitor™ DieselPower BioEnhancer is a fuel treatment additive used to improve fuel quality and efficiency that can degrade through heat and oxidation. It can also help maintain color and stability of the fuel as well as control corrosion issues.



## Product information

Unitor™ DieselPower BioEnhancer is a high-performance multifunctional treatment designed for diesel fuel or biofuels and bio-blends and lighter fuels in general. The product improves the quality of the fuel, providing a range of benefits for different types of engines and fuel systems . It can help improve engine performance, fuel stability, and emissions.

### Features

- Can be applied in fuels with a broad range of FAME/HVO content
- Removes and prevents injector deposits in both direct injection (DI) and indirect injection (IDI) engines
- Prevents metal leaching into the fuel
- Reduces the foaming tendency of diesel fuel
- Has good water separability

### Benefits

- Provides strong protection of the fuel system against corrosion
- Increases the conductivity of diesel fuel and biofuels
- Improves the oxidation stability of diesel fuel and biofuels
- Can have positive effects on emissions and fuel consumption depending on vessel types and conditions

## Specification

### General

Invent Hazard Material (IMO/IU) classification	C-6
--	-----

### Physical properties

Density [kg/dm3]	0.922
Flash Point [°C]	>61
Form	Liquid
Pour Point [°C]	>-51
Viscosity	9.6 cSt

## Documents

[SDoC and MD for IHM](#)

## Directions for use

DieselPower BioEnhancer may be applied directly to bunkers or storage tanks but for best mixing should be applied to feed lines during filling.

Unitor™ Dielelpower BioEnhancer is recommended to be dosed as 1:5000 (1 litre: 5 MT of fuel).

DieselPower BioEnhancer is suitable to be used with carbon steel, stainless steel and fluorinated polyethylene materials present in storage tanks and injection systems. Polyethylene, rubber, polystyrene and polypropylene should be avoided.

## Related products

Is frequently bought together with

- 779112**  
DIESELPower CFPP 25 LTR
- 779094**  
DIESELPower LUBRICITY 25 LTR
- 764493**  
UNITOR BACTERIA SINGLE TEST KIT
- 779082**  
DIESELPower BIOCONTROL 25 LTR
- 673155**  
UNITOR EASYSHIP WATER TEST KIT

