

Last updated: 01/05/2024 07:23:06

FUEL POWER CONDITIONER 25 LTR

Product group: **650** Product number: **778785**

Unitor[™] FuelPower[™] Conditioner is the market leading solution for asphaltenic sludge control as well as keeping fuel tanks clean. The product works with HSFO and the new VLSFO introduced through IMO 2020. Sedimentation of residual fuels is a common problem and can be reduced with Unitor[™] FuelPower[™] Conditioner.



Product information

This product supersedes product no: **766154**

Fuel stability and compatibility is an increasing problem with modern marine heavy fuels, especially with blending of low sulfur fuels.

The solution for handling these unstable and incompatible fuels is Unitor[™] FuelPower[™] Conditioner, it stabilizes and stops sludge formation in fuel tanks.

Unitor[™] FuelPower[™] Conditioner also improves separation reducing the amount of sludge wasted keeping the fuel homogeneous through the whole fuel system delivering a stable fuel ready for combustion.

Features

- Stabilizes fuel blends, reducing compatibility problems
- Disperses and prevents sludge formation
- Reduces the amount of sludge wasted in the centrifugal separator

Benefits

- The conditioning properties of Unitor[™] FuelPower[™] Conditioner ensures your fuel is stable and that a minimum of sludge is wasted in tanks and centrifugal separators
- With purifier working efficiently, filters clean and fuel system in good shape you can focus on the important things

Specification

General

Invent Hazard Material (IMO/EU) classification	C-6
--	-----

Physical properties

Appearance	Clear, light brown
Density [kg/dm ³]	0,84
Flash Point [°C]	>61
Form	Liquid

Technical data

Not Compatible	May swell rubber and synthetic rubber
----------------	---------------------------------------

Documents

[SDoC and MD for IHM](#)

[No Objection Letter Wartsila](#)

Directions for use

Dosage and Control

Ideally, FuelPower Conditioner should be dosed directly into the bunker tank prior to bunkering. However, it can be introduced to the settling tank or during transfer from storage. Dosage rates are best determined from the results of fuel analysis, i.e. sediment content or compatibility test which is easily performed on board using the Compatibility Test Kit.

ASTM SPOT	1	2	3	4	5
DOSE RATE	**1:25 000	1:15 000	1:10000	1:5000	*1:2500

TSP level	Dosage (ppm)	Comment
0,01–0,03	1:25 000 (40 ppm)	Due to the indication of poor reserve stability of some VLSFO, we advise a low protective dosage.
0,03–0,06	1:20 000 (50 ppm)	When the TSP increases the reserve stability of the fuel will also be poorer, so we advise a low protective dosage.
0,06–0,1	1:15 000 (67 ppm)	Once the TSP approaches the max specification sludging will most likely occur. Reserve Stability will also be poor, so a higher dosage is recommended.
0,1–0,2	1:10 000 (100 ppm)	With a TSP out of specification it is important to have a good impact on the sludging with a higher dosage.
0,2–0,5	1:5 000 (200 ppm)	A far-off spec TSP fuel is never a good idea to use but when it occurs it is important to be able to reduce sludging and operational impact as much as possible.
*0,5+	1:1 000 (1000 ppm)	We would not recommend using any of these fuels but if there is no choice a high dosage needs to be used to have a chance to reduce the sludging from these fuels

* Avoid using this fuel if possible.

** Fully compatible blends, with a sediment percentage of less than 0.05, should not require treatment for incompatibility. Marginal number 1 spots may cause sludging if the fuel is not handled carefully, so some treatment may be necessary, especially if other problems such as water content or corrosion are apparent.

Fuel tank cleaning The average dosage for FuelPower Conditioner is 1:15 000 or 67 ppm. When starting a dosage into a fuel tank it is advisable to use a staged dosage to avoid high amounts of sludge from the fuel into purifiers and filters. This is especially important if the fuel tank has not been cleaned for an extended period of time. With a stage dosing smaller amounts of sludge will be picked up and over a longer period of time.

DOSING	DOSAGE LEVEL	COMMENT
1st Time	1:25 000	Initial dosage not to upset the tank
2nd Time	1:20 000	Second and third dosages can be done a bit higher as most of the easily available sludge will be gone
3rd time and forward	1:15 000	From the 3rd dosage and forward the recommended dosage of 1:15 000 can be used

Related products

Is frequently bought together with

765018
ENVIROCLEAN 25 LTR

773153
UNITOR COMPATIBILITY TEST KIT

571364
VAPTREAT 25LTR

698720
AUTOTREAT - 25 LTR

571687
DISCLEAN 25 LTR

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/fuel-oil-chemicals/heavy-fuel-oil-treatment/fuel-power-conditioner-25-ltr/>