

Last updated: 23/02/2023 08:41:21

UNITOR COMPATIBILITY TEST KIT

Product group: **663** Product number: **773153**

Being able to understand the compatibility of your fuel is very important. When the fuel is bunkered it is difficult to understand the condition of the fuel, how stable it is and if it needs any sort of help to remain stable.

With the Unitor Compatibility Test Kit you can easily and quickly get an assessment on the stability and compatibility of the fuel you are bunkering. It gives piece of mind if the test looks good but more importantly it gives you time to correct any issues before the vessel leaves port.



Product information

This product supersedes product no: **555755**

The Unitor™ Oil Compatibility Tester is the perfect way to make sure your delivery of your VLSFO fuel is stable and compatible. The Tester shows you if the fuel is in danger from asphaltenic sludge formation. It also provides a quick and easy tool for understanding fuel compatibility necessary to mix or blend residual fuel oil. Ultimately, it will give you a quick picture about the stability and compatibility of your fuel.

Features

- Small and compact, completely portable
- Specifically designed for onboard use
- No reagents, no glassware, disposable sample containers and No cleaning
- Complete with guide on methods to prevent sludging

Benefits

- Portable, easy to use and suitable to work onboard the vessels
- Results can be used to determine if pre combustion additives are required and to assess dose rate
- Confirm that the fuel delivery will remain stable in the bunker tanks
- Identify possible stability problems before mixing two fuels
- Help prevent sludge deposits, failure of fuel handling systems and costly combustion related engine damage

Specification

General

Invent Hazard Material (IMO/EU) classification	D-1
-------------------------------------------------------	-----

Dimensions/Weight

Dimensions L x W x H [mm]	340 x 385 x 170
Weight [kg]	3.7

Technical data

Power [W]	110-220 VAC (Autoselected) rated
------------------	----------------------------------

Performance data

Range	As per ASTM D-4740
Test time	20 min (Unattended)

Documents

[773153-Compatibility-Test-Kit](#)

[Overview-773153-Compatibility-Test-Meter](#)

[SDoC and MD for IHM](#)

Related products

Consumables

- 555789**
COMPATIBILITY TEST PAPER (100 SHEETS)
- 555771**
COMPATIBILITY SAMPLE TUBE 1 PACK OF 25 PIECES

Is frequently bought together with

571653
DESCALING LIQUID 25 LTR

571364
VAPTREAT 25LTR

571356
ROCOR NB LIQUID 25 LTR

698720
AUTOTREAT - 25 LTR

571687
DISCLEAN 25 LTR

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/test-kits-and-reagents/oil-test-kits/unitor-compatibility-test-kit>