

Last updated: 27/06/2024 01:01:15

OXYTREAT 25 LTR

Product group: **655** Product number: **777713**

NALFLEET™ Oxytreat™ is a blend of selected tannins for corrosion protection in low to medium pressure steam boilers



Product information

This product supersedes product no: **777241**

Features

- Iron/tannate film protects metal surface
- Removes oxygen, protecting boiler and steam lines
- Low toxicity
- Protects feed tank and feed lines

Benefits

- Protects feed tank, feed lines and boiler metal
- Does not add to boiler TDS

Specification

General

Invent Hazard Material (IMO/IU) classification	C-9
---	-----

Physical properties

Appearance	Brown
Density [g/ml]	1.1
Form	Liquid
pH	5.2 to 6.0

Documents

[SDoC and MD for IHM](#)

Directions for use

NALFLEET™ Oxytreat is formulated to provide corrosion protection for the feed and boiler system and when used in conjunction with Multi-plus provides a total treatment programme.

Dosing Method

NALFLEET™ Oxytreat is best applied by continuous injection to the boiler feed tank using a suitable chemical metering pump to maintain the target reserve in the boiler. NALFLEET™ Oxytreat is normally dosed at around 15mls per ton of steam to provide 120-160 ppm of tannin in the boiler water,

Sampling and Testing

NALFLEET™ Oxytreat is best applied neat or diluted with condensate or evaporated water to any convenient strength using a suitable chemical dosing pump. The product should be applied to the boiler feed tank or feed line to ensure adequate mixing.

Related products

Accessories

Test Kits for Tannin, P Alkalinity, Chloride and Nitrite

777100
BOILER PLUS TEST KIT M0380.

Is frequently bought together with

680843
COOLTREAT AL 25 LTR

571356
ROCOR NB LIQUID 25 LTR

735977
MAR-71 BIOCID 3X5L NOT IN USA&CAN

638676
EVAPORATOR DEFOAMER 4X5 LTR

698720

AUTOTREAT - 25 LTR

777710

NALFLEET 2000 25 LTR

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/water-treatment-chemicals/boiler-water-treatment/oxytreat-25-ltr>