

Last updated: 08/08/2024 06:47:25

# TIMM MASTER 8 TAIL 64MM 22M WHITE 2X2,0M EYE

Product group: 325 Product number: L412057

## Product information

### Specification

#### General

Invent Hazard Material (IMO/ELJ) classification	NA
Material	75% Polyolefin / 25% HT Polyester
Material type and grade	Mxed polyolefins (B5 yarn) and HT PES

#### Physical properties

Colour	White with 3 black marking yarns
Construction	8-strand plaited
Density	0.99
Eyes	1,8mmesh braid protected eyes
Jacketed	false
Line Construction	8-strand braided
Line Linear Density (LLD)	2.137 kg/m
Line Tenacity (LT) Maximum	38.41 t/kg/m
Line Tenacity (LT) Maximum (kN/g/m)	0.38 kN/g/m
Line Tenacity (LT) Measured	37.85 t/kg/m
Load Bearing Linear Density (LBLD)	2.137 kg/m
Melting point	165°C
NSBF (if requested)	Not requested
Rotating	false
Splice type and design	Tuck (4S-4Z)x5

#### Dimensions/Weight

Diameter [mm]	74
Dimensions	64
Length	22

#### Technical data

Average Immediate Strain (e) %\LDBF:10	1.24
Average Immediate Strain (e) %\LDBF:20	2.50
Average Immediate Strain (e) %\LDBF:30	3.71
Average Immediate Strain (e) %\LDBF:40	4.82
Average Immediate Strain (e) %\LDBF:50	5.88
Dynamic stiffness (Kex) Exposed	18.896xTDBF
Dynamic stiffness (Ksh) Sheltered	13.637xTDBF
Line Design Break Force (LDBF)	80.9
Spliced MBL DRY [kN]	80.9
Spliced MBL/LDBF [kN]	794
Tension-tension endurance CTF 20%	2675208408,5
Tension-tension endurance CTF 50%	701711
Unspliced MBL [t]	89.9

#### Performance data

DNVGL	Y
SBA	N
Strength adjustment	10%
Var Range From	125%
Var Range To	130%

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/ropes/rope-stretchers/timm-master-8-tail/timm-master-8-tail-64mm-22m-white-2x20m-eye/>