

Last updated: 13/02/2023 14:12:04

## GPR-300H 6.0X450MM 23 PCS 5.3KG

Product group: **095**    Product number: **699260**

High recovery electrode for welding of mild steel and used especially for heavy lifter sea fastening application.



### Product information

This product supersedes product no: **658179**

High recovery rutile type electrodes for unalloyed steels. Easy to use in the horizontal position with a speed of up to 50 cm/min., and a throat thickness up to 3.5 - 6 mm in one layer. Self-releasing slag. Also suited for steels protected with zinc- or iron-oxide based primers.

#### Features

- Unitor high density polyethylene packing
- High deposition rate with low spatters
- Can be rested in the joint during welding
- Approved by classification societies for mild steels

#### Benefits

- Long storage lifespan without moisture pick up
- Greatly improves on the time to do the job
- Makes the welding easy to perform
- In compliance with maritime rules and regulations

### Specification

#### General

Invent Hazard Material (IMO/EU) classification	NA
--	----

#### Dimensions/Weight

Diameter [mm]	6
Weight [kg]	5.3

#### Technical data

AWS	E7024
Polarity	AC/DC +/-

#### Performance data

Amperage [A]	430
--------------	-----

### Approvals

Contact Customer Service for 3rd party approvals certificates

### Documents

[SDoC and MD for IHM](#)

### Related products

Is frequently bought together with

- 758458**  
ACA-384 15X5X305MM50 PCS 2.1 KG
- 633263**  
SHADE 11 GLASS. 5SET
- 699306**  
LHH-314H 5.0X450MM36 PCS 5.5 KG
- 699256**  
GPR-300H 5.0X450MM35 PCS 5.6 KG
- 758466**  
ACA-384 8.0X305MM50 PCS 1.3 KG

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/gpr-300h-6.0x450mm-23-pcs-5.3kg>