

Last updated: 30/08/2023 04:45:46

# LH-314N 2.5X350MM 161 PCS 4.0 KG

Product group: **095** Product number: **699264**

Low hydrogen, high tensile electrode for welding of mild steel and ship quality steel.



## Product information

This product supersedes product no: **605857**

A reliable basic all-around LMA electrode for unalloyed and low alloyed ship quality steels, high deposition rate, deposit with high resistance against impact and cracking. Easily removable slag, good building properties.

### Features

- LMA electrode
- Unitor high density polyethylene packing
- Approved by classification societies for higher tensile steels
- Deposit recovery 129%

### Benefits

- Optimised formula for shipboard maintenance welding giving high deposition and excellent performance
- Electrodes can be exposed longer in the open
- Long storage lifespan without moisture pick up
- In compliance with maritime rules and regulations

## Specification

### General

Invent Hazard Material (IMO/EU) classification	NA
--	----

### Dimensions/Weight

Diameter [mm]	2.5
Weight [kg]	4

### Technical data

AWS	E 7018
Polarity	DC +/-

### Performance data

Amperage [A]	105
--------------	-----

## Approvals

Contact Customer Service for 3rd party approvals certificates

## Documents

[SDoC and MD for IHM](#)

## Related products

Is consumable by

**669999**  
ELECTRODE CABINET COMPACT EMPTY

Is frequently bought together with

**699405**  
18/8-321N 2.5X300MM 89 PCS 1.7 KG

**233601**  
AG 60 252 2.0 X 500MM 0,5KG

**699173**  
GPO-302N 3.2X350MM 190 PCS 5.4 KG

**699165**  
GPO-302N 2.5X350MM 295 PCS 5,2KG

**699272**  
LH-314N 3.2X450MM 96 PCS 5KG

**150150**

UWI-150 TP WELDING INVERTER IN CASE (1P 230V)

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/lh-314r-2.5x350mm-161-pcs-4.0-kg>