

Last updated: 25/08/2023 00:00:41

LH-314N 3.2X450MM96 PCS 5KG

Product group: **095** Product number: **599272**

Low hydrogen, high tensile electrode for welding of mild steel and ship quality steel.



Product information

This product supersedes product no: **699272**

A reliable basic all-around LMA electrode for unalloyed and low alloyed ship quality steels, high deposition rate, deposit with high resistance against impact and cracking. Easily removable slag, good building properties.

Features

- LMA electrode
- Unitor high density polyethylene packing
- Approved by classification societies for higher tensile steels
- Deposit recovery 124%

Benefits

- Optimised formula for shipboard maintenance welding giving high deposition and excellent performance
- Electrodes can be exposed longer in the open
- Long storage lifespan without moisture pick up
- In compliance with maritime rules and regulations

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Dimensions/Weight

Diameter [mm]	3.2
Weight [kg]	5

Technical data

AWS	E7018
Polarity	DC +/-

Performance data

Amperage [A]	155
--------------	-----

Approvals

Contact Customer Service for 3rd party approvals certificates

Documents

[SDoC and MD for IHM](#)

Related products

Is frequently bought together with

699280
LH-314N 4.0X450MM78 PCS 5.6 KG

699264
LH-314N 2.5X350MM161 PCS 4.0 KG

699165
GPO-302N 2.5X350MM295 PCS 5,2KG

699173
GPO-302N 3.2X350MM190 PCS 5.4 KG

320320
UWI-320TP WELDING INVERTER

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/lh-314n-3.2x450mm96-pcs-5kg>