

Last updated: 24/08/2023 00:00:39

# LH-314N 4.0X450MM 78 PCS 5.6 KG

Product group: **095** Product number: **599280**

Low hydrogen, high tensile electrode for welding of mild steel and ship quality steel.



## Product information

This product supersedes product no: **699280**

A reliable basic all-around LMA electrode for unalloyed and low alloyed ship quality steels, high deposition rate, deposit with high resistance against impact and cracking. Easily removable slag, good building properties.

### Features

- LMA electrode
- Unitor high density polyethylene packing
- Approved by classification societies for higher tensile steels
- Deposit recovery 118%

### Benefits

- Optimised formula for shipboard maintenance welding giving high deposition and excellent performance
- Electrodes can be exposed longer in the open
- Long storage lifespan without moisture pick up
- In compliance with maritime rules and regulations

## Specification

### General

Invent Hazard Material (IMO/EU) classification	NA
------------------------------------------------	----

### Dimensions/Weight

Diameter [mm]	4
Weight [kg]	5.6

### Technical data

AWS	E7018
Polarity	DC +/-

### Performance data

Amperage [A]	210
--------------	-----

## Approvals

Contact Customer Service for 3rd party approvals certificates

## Documents

[SDoC and MD for IHM](#)

## Related products

Is frequently bought together with

**699181**  
GPO-302N 4.0X350MM 120 PCS 5.2 KG

**699173**  
GPO-302N 3.2X350MM 190 PCS 5.4 KG

**699264**  
LH-314N 2.5X350MM 161 PCS 4.0 KG

**699272**  
LH-314N 3.2X450MM 96 PCS 5KG

**320320**  
UWI-320TP WELDING INVERTER

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/lh-314n-4.0x450mm-78-pcs-52.6-kg>