

Last updated: 15/02/2023 03:43:56

# LHH-314H 4.0X450MM 54 PCS 5.5 KG

Product group: **095** Product number: **699298**

High recovery electrode for welding of mild and ship quality steel with good charpy impact value.



## Product information

High recovery basic type LMA electrode for unalloyed and low alloyed ship quality steels. Easy to use in the flat position by doing contact welding.

### Features

- LMA electrode
- Unitor high density polyethylene packing
- High deposition rate
- Can be rested in the joint during welding
- Approved by classification societies for higher tensile steels

### Benefits

- Electrodes can be exposed longer in the open
- Long storage lifespan without moisture pick up
- Greatly improve on the time to do the job
- Makes the welding easy to perform
- In compliance with maritime rules and regulations

## Specification

### General

Invent Hazard Material (IMO/EU) classification	NA
--	----

### Dimensions/Weight

Diameter [mm]	4
Weight [kg]	5.5

### Technical data

AWS	E 7028
Polarity	AC, DC+

### Performance data

Amperage [A]	240
--------------	-----

## Documents

[SDoC and MD for IHM](#)

## Related products

Is frequently bought together with

**905034**  
OXYGEN O-40 FILLING

**905026**  
ACETYLENE A-40 FILLING

**699165**  
GPO-302N 2.5X350MM 295 PCS 5,2KG

**699173**  
GPO-302N 3.2X350MM 190 PCS 5.4 KG

**699272**  
LH-314N 3.2X450MMØ6 PCS 5KG

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/lhh-314h-4.0x450mm-54-pcs-5.5-kg>