

Last updated: 15/02/2023 03:44:12

# LHH-314H 5.0X450MM 36 PCS 5.5 KG

Product group: 095 Product number: 699306

High recovery electrode for welding of mild and ship quality steel with good charpy impact value.



## Product information

High recovery basic type LMA electrode for unalloyed and low alloyed ship quality steels. Easy to use in the flat position by doing contact welding.

### Features

- LMA electrode
- Unitor high density polyethylene packing
- High deposition rate
- Can be rested in the joint during welding
- Approved by classification societies for higher tensile steels

### Benefits

- Electrodes can be exposed longer in the open
- Long storage lifespan without moisture pick up
- Greatly improve on the time to do the job
- Makes the welding easy to perform
- In compliance with maritime rules and regulations

## Specification

### General

Invent Hazard Material (IMO/EU) classification	NA
--	----

### Dimensions/Weight

Diameter [mm]	5
Weight [kg]	5.5

### Technical data

AWS	E 7028
Polarity	AC, DC+

### Performance data

Amperage [A]	355
--------------	-----

## Documents

[SDoC and MD for IHM](#)

## Related products

Is frequently bought together with

**699165**  
GPO-302N 2.5X350MM295 PCS 5,2KG

**699264**  
LH-314N 2.5X350MM161 PCS 4.0 KG

**699260**  
GPR-300H 6.0X450MM23 PCS 5.3KG

**699272**  
LH-314N 3.2X450MM96 PCS 5KG

**699280**  
LH-314N 4.0X450MM78 PCS 5.6 KG

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/lhh-314h-5.0x450mm-36-pcs-5.5-kg>