

Last updated: 26/06/2023 13:39:39

# LHT-318N 3.2X350MM 48 PCS 1.7 KG

Product group: **095** Product number: **699348**

Electrode for welding of high temperature steel e.g. boiler plates or pipes.



## Product information

This product supersedes product no: **606450**

Low hydrogen and LMA basic coated electrode for heat resistant low alloy steels with up to 1% Chromium an 0.5% Molybdenum. Used on boiler plates and pipes for working temperatures up to 550°C.

### Features

- LMA electrode
- Unitor high density polyethylene packing
- Approved by classification societies for boiler tubes and boiler plates with 1%Cr, 1/2% Mb and temp. up to 550°C

### Benefits

- Electrodes can be exposed longer in the open
- Long storage lifespan without moisture pick up
- In compliance with maritime rules and regulations

## Specification

### General

Invent Hazard Material (IMO/EU) classification	NA
------------------------------------------------	----

### Dimensions/Weight

Diameter [mm]	2.5
Weight [kg]	1.7

### Technical data

AWS	E 8018-B2
Polarity	DC+/-

### Performance data

Amperage [A]	150
--------------	-----

## Documents

[SDoC and MD for IHM](#)

## Related products

Is frequently bought together with

- 233601**  
AG 60 252 2.0 X 500MM 0,5KG
- 699165**  
GPO-302N 2.5X350MM 295 PCS 5,2KG
- 699173**  
GPO-302N 3.2X350MM 190 PCS 5.4 KG
- 699330**  
LHT-318N 2.5X350MM 75 PCS 1.7 KG
- 699272**  
LH-314N 3.2X450MM 96 PCS 5KG

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/lht-318n-3.2x350mm-48-pcs-1.7-kg>