

Last updated: 04/11/2023 02:00:42

LHV-316N 3.2X350MM 137 PCS 4.8 KG

Product group: **095** Product number: **699314**

Vertical down welding electrode for welding of mild steel and ship quality steel.



Product information

This product supersedes product no: **592949**

Low hydrogen and LMA heavily coated basic electrode for unalloyed and low alloyed ship quality steels, especially suited for vertical down welding in addition to other positions. Practically self-releasing slag, high deposition rate.

Features

- LMA electrode
- Unitor high density polyethylene packing
- Vertical down welding
- Can be rested in the joint during welding
- Approved by classification societies for higher tensile steels

Benefits

- Electrodes can be exposed longer in the open
- Long storage lifespan without moisture pick up
- Greatly improve on the time to do the job
- Makes the welding easy to perform
- In compliance with maritime rules and regulations

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Dimensions/Weight

Diameter [mm]	3.2
Weight [kg]	4.8

Technical data

AWS	E 8018-G
Polarity	DC+

Performance data

Amperage [A]	150
--------------	-----

Documents

[SDoC and MD for IHM](#)

Related products

Is frequently bought together with

699165
GPO-302N 2.5X350MM 295 PCS 5,2KG

699173
GPO-302N 3.2X350MM 190 PCS 5.4 KG

632786
WELDERS GLOVES. 6 PAIRS

699264
LH-314N 2.5X350MM 161 PCS 4.0 KG

699272
LH-314N 3.2X450MM 96 PCS 5KG

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/lhv-316n-3.2x350mm-137-pcs-4.8-kg>