

Last updated: 15/02/2023 03:49:44

# LHV-316N 4.0X350MM 99 PCS 5.0 KG

Product group: **095** Product number: **699322**

Vertical down welding electrode for welding of mild steel and ship quality steel.



## Product information

This product supersedes product no: **592956**

Low hydrogen and LMA heavily coated basic electrode for unalloyed and low alloyed ship quality steels, especially suited for vertical down welding in addition to other positions. Practically self-releasing slag, high deposition rate.

### Features

- LMA electrode
- Unitor high density polyethylene packing
- Vertical down welding
- Can be rested in the joint during welding
- Approved by classification societies for higher tensile steels

### Benefits

- Electrodes can be exposed longer in the open
- Long storage lifespan without moisture pick up
- Greatly improve on the time to do the job
- Makes the welding easy to perform
- In compliance with maritime rules and regulations

## Specification

### General

Invent Hazard Material (IMO/EU) classification	NA
--	----

### Dimensions/Weight

Diameter [mm]	4
Weight [kg]	5

### Technical data

AWS	E 8018-G
Polarity	DC+

### Performance data

Amperage [A]	220
--------------	-----

## Documents

[SDoC and MD for IHM](#)

## Related products

Is frequently bought together with

- 699181**  
GPO-302N 4.0X350MM 120 PCS 5.2 KG
- 699165**  
GPO-302N 2.5X350MM 295 PCS 5,2KG
- 699173**  
GPO-302N 3.2X350MM 190 PCS 5.4 KG
- 699314**  
LHV-316N 3.2X350MM 137 PCS 4.8 KG
- 699215**  
SPECIAL-303N 3.2X350MM 120PCS 4,1KG

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/lhv-316n-4.0x350mm-99-pcs-5.0-kg>