

Last updated: 19/06/2023 10:33:11



Product number: 175828

Welding cable 50mm<sup>2</sup> x 10m with safety cable connectors.

### **Product information**

Welding cables used on board, on deck or in an engine room, are exposed to rough weather, oil and mechanical wear. The welding cable supplied by Unitor has wear, flame and oil-resistant insulation on a polychloroprene rubber basis.

It is recognized by its marking at regular intervals with the text "Unitor oil resistant welding cable", size of cable, and the standard for welding cable H01N2-D.

The cable is available in cross section areas 35mm<sup>2</sup>, 50mm<sup>2</sup> 70mm<sup>2</sup>, and 95mm<sup>2</sup>.

#### **Features**

- The cable marked H01N2-D means that it is produced to an international harmonized standard
- The standard length cable extensions are fitted with Unitor safety cable connectors for optimal protection. Connection to the machine panel sockets is done with 2 pcs Dix/Unitor conversions
- When cable extensions with safety connectors are used the electrode holder and ground clamp with safety connectors should be used

#### Benefits

- Unitor welding cable is oil resistant, flame resistant and wear resistant
- The conductor is built up from 0.2mm diameter copper wires to ensure high flexibility

## **Specification**

Dimensions/Weight General

Invent Hazard Material (IMO/EU) classification NΑ Weight [kg] 5.7

Performance data

Amperage [A] 480 Maximum Amperage 35% duty cycle

## **Documents**

### SDoC and MD for IHM

# **Related products**

Is frequently bought together with

175596

HOSE JOINT F/6MM (1/4 INCH) OX HOSE

175588

HOSE JOINT F/6MM (1/4 INCH) AC HOSE

632893

CABLE CONNECTOR DIX70 MALE-FEMALE

633206

SPARE FLINT SET. 10 PCS

175810

WELDING CABLE & CONNECTOR 50 MW2 20M

This page is printed from