

Last updated: 29/11/2023 15:17:51

FLOWCONTROL METER, ARGON

Product group: 197 Product number: 597328

Flowcontrol meter for shielding gases either UNIMIX (Ar/CO2) or Argon for use at torch nozzle to measure flow rate.

Product information

Actual gas flow at the TIG or wire torch may deviate from what is set on the gas outlet station or on the cylinder regulator, especially if long gas hoses are used. The flowcontrol meter measures actual flow at the torch nozzle and is a useful tool for the operator.

Features

- Measure flow rate in L/min
- Can be used on TIG Torch (T-150, T-200) or Gas Shielded Wire Torch such as T-400

Benefits

- Ensure good welding quality with precise shielding gas flow rate
- Ensure precise use of shielding gas to avoid wastage

Specification

General

Invent Hazard Material (IMO/EU) classification

NΑ

Documents

597328-DoC

SDoC and MD for IHM

Related products

Is accessory to

203203

UWI-203 TP WELDING INVERTER

500500

UWI-500TP WELDING INVERTER

500102

UWF-102 WIRE FEEDER FOR UWI-500TP

320320

UWI-320TP WELDING INVERTER

301301

UWW-301 TP WRE WELDER

Is frequently bought together with

510010

REGULATOR 510 AR/CO2 FLOW 0-35L/MIN

607810

TIG TORCH ACCESSORIES KIT

632794

TIG GLOVES. 6 PAIRS

597310

FLOWCONTROL VALVE, ARGON

200000

TIG TORCH T-200 W.DIX 70 CONNECTOR

This page is printed from

https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-equipment/shielding-gas-accessories/flowcontrol-meter-argon/

