

Last updated: 26/06/2023 13:39:41

SHADE 11 GLASS. 5SET

Product group: **196** Product number: **633263**

Filter glasses for arc welding



Product information

This product supersedes product no: **175687**

For use from 80-175 A, the glasses have dimension 60 x 110 mm and are manufactured in accordance with DIN standard and are CE approved. When ordering face shields, filter shade glass of correct shade should be ordered in addition to the filter shade 11 glasses which are included. The filter glasses are supplied in sets consisting of 5 safety glasses, 5 protection glasses and 5 filter shade glasses.

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Approvals

CE

Documents

[SDoC and MD for IHM](#)

Directions for use

<p>A. Safety glass (polycarbonate)</p> <p>The glass is used in shields with a flip-up front frame and should be placed nearest to the eyes to protect against slag or other articles while chipping/ grinding when the flip up front is open.</p>
<p>B. Filter shade glass</p> <p>Filters out harmful infra-red and ultra-violet rays from the welding arc, and reduces visible light to a level which is sufficient to see the welding process without straining the welder's eyes. Filter Shade Glass should be selected based on welding process and amperage. The glasses are marked Protane Shade SO 1 DIN 0196 CE</p>
<p>C. Protection glass</p> <p>The glass is placed in front of the filter shade glass to protect gainst spatter. The protection glass should be replaced at regular intervals.</p>

Related products

Is accessory to

709485
FLIPVISION WELDING FACE SHIELD

619098
FACE SHIELD W/HANDLE

619114
SAFETY HELM W/FACE SH.

Is frequently bought together with

905034

OXYGEN O-40 FILLING

699165

GPO-302N 2.5X350MM295 PCS 5,2KG

699173

GPO-302N 3.2X350MM190 PCS 5.4 KG

632786

WELDERS GLOVES. 6 PAIRS

633214

PROTECTION GLASS. 10PCS

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/welding/arc-welding-equipment/welders-protection/shade-11-glass.-5set>