

Last updated: 30/03/2023 21:02:26

CUTTING NOZZLE 10- 25MM

Product group: **170** Product number: **174706**

The cutting nozzles are specially made for use with UCT-500 gas cutting equipment and with oxy/acetylene gases.



Product information

Nozzles should be selected based on cutting thickness. The basic information is marked directly on the nozzle i.e.:

Nozzle nr 3
Material thickness 10-25 mm Gas consumption OX: 2150nl/h,
AC: 520nl/h

Features

- Designed for use with oxy/acetylene
- Made from high quality copper alloys
- Machined to precision for correct seating angle to prevent any gas leakages and uniform gas holes

Benefits

- Made with the highest safety in mind for equal pressure torch
- Good cutting performance
- Durable

Specification

General

Invent Hazard Material (IMO/IU) classification	NA
--	----

Documents

[SDoC and MD for IHM](#)

[cutting-nozzle](#)

Related products

Is accessory to

- 500001**
UCT-500 COMBINATION TORCH COMPACT
- 500000**
UCT-500 COMBINATION TORCH MASTER
- 234807**
CUTTING ATTACHMENT 90 DGR
- 174664**
CUTTING ATTACHMENT 75 DGR
- 234815**
CUTTING ATTACHMENT 0 DGR

Is part of bundle

- 589861**
GASWELDING CABINET COMPLETE

Is frequently bought together with

- 905034**
OXYGEN O-40 FILLING
- 905026**
ACETYLENE A-40 FILLING
- 510000**
REGULATOR 510 OX PRESSURE 0-10 BAR
- 699173**
GPO-302N 3.2X350MM 190 PCS 5.4 KG

174698
CUTTING NOZZLE 3- 10MM

This page is printed from
<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/welding-brazing--cutting-torch/cutting-nozzle-10--25mm/>