

Last updated: 26/06/2023 13:39:38

## CUTTING NOZZLE 3- 10MM

Product group: **170** Product number: **174698**

The cutting nozzles are specially made for use with UCT-500 gas cutting equipment and with oxy/acetylene gases.



### Product information

Nozzles should be selected based on cutting thickness. The basic information is marked directly on the nozzle i.e.:

Nozzle nr 2 Material thickness 3-10 mm Gas OX 1300 nl/h Consumption AC 460 nl/h

#### Features

- Designed for use with oxy/acetylene
- Made from high quality copper alloys
- Machined to precision for correct seating angle to prevent any gas leakages and uniform gas holes

#### Benefits

- Made with the highest safety in mind for equal pressure torch
- Good cutting performance
- Durable

### Specification

#### General

Invent Hazard Material (IMO/EU) classification	NA
--	----

### Documents

[SDoC and MD for IHM](#)

[cutting-nozzle](#)

### Related products

Is accessory to

**500001**  
UCT-500 COMBINATION TORCH COMPACT

**500000**  
UCT-500 COMBINATION TORCH MASTER

**234807**  
CUTTING ATTACHMENT 90 DGR

**174664**  
CUTTING ATTACHMENT 75 DGR

**234815**  
CUTTING ATTACHMENT 0 DGR

Is part of bundle

**589861**  
GASWELDING CABINET COMPLETE

Is frequently bought together with

**905034**  
OXYGEN O-40 FILLING

**905026**  
ACETYLENE A-40 FILLING

**510000**  
REGULATOR 510 OX PRESSURE 0-10 BAR

**699173**  
GPO-302N 3.2X350MM 190 PCS 5.4 KG

**174706**  
CUTTING NOZZLE 10- 25MM

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/welding-brazing--cutting-torch/cutting-nozzle-3--10mm>