

Last updated: 26/06/2023 13:39:39

# CUTTING NOZZLE 50-100MM

Product group: 170      Product number: 174722

The cutting nozzles are specially made for use with UCT-500 gas cutting equipment and with oxy/acetylene gases.



## Product information

Nozzles should be selected based on cutting thickness. The basic information is marked directly on the nozzle i.e.:

Nozzle no 5 Material thickness 50-100 mm Gas consumption OX: 7800nl/h  
AC: 810nl/h

### Features

- Designed for use with oxy/acetylene
- Made from high quality copper alloys
- Machined to precision for correct seating angle to prevent any gas leakages and uniform gas holes

### Benefits

- Made with the highest safety in mind for equal pressure torch
- Good cutting performance
- Durable

## Specification

### General

|                                                |    |
|------------------------------------------------|----|
| Invent Hazard Material (IMO/EU) classification | NA |
|------------------------------------------------|----|

## Documents

[cutting-nozzle](#)

[SDoC and MD for IHM](#)

## Related products

Is accessory to

**500000**  
UCT-500 COMBINATION TORCH MASTER

**234807**  
CUTTING ATTACHMENT 90 DGR

**174664**  
CUTTING ATTACHMENT 75 DGR

**234815**  
CUTTING ATTACHMENT 0 DGR

Is part of bundle

**589861**  
GASWELDING CABINET COMPLETE

Is frequently bought together with

**510001**  
REGULATOR 510 AC PRESSURE 0-1.5 BAR

**510000**  
REGULATOR 510 OX PRESSURE 0-10 BAR

**174706**  
CUTTING NOZZLE 10- 25MM

**174698**  
CUTTING NOZZLE 3- 10MM

**174714**  
CUTTING NOZZLE 25- 50MM

