

Last updated: 19/06/2023 10:33:11

WELDING ATTACHMENT 230 L

Product group: 170 Product number: 174581

The welding attachment is used in combination with UCT-500 torch shank for brazing and gas welding.



Product information

The selection of welding attachment with different gas flow rate / capacity will determine the workable material thickness range.

Size* O-A230 for material thickness: 2.0 -3.0 mm

The size indicates consumption of Oxygen in nl/h. Acetylene consumption is approximately 10% lower. Material thickness refers to mild steel.

Specification

General

Invent Hazard Material (IMO/IU) classification	NA
--	----

Documents

[SDoC and MD for IHM](#)

Related products

Is accessory to

500001
UCT-500 COMBINATION TORCH COMPACT
500000
UCT-500 COMBINATION TORCH MASTER

Is part of bundle

589861
GASWELDING CABINET COMPLETE

Is frequently bought together with

510001
REGULATOR 510 AC PRESSURE 0-1.5 BAR
510000
REGULATOR 510 OX PRESSURE 0-10 BAR
174706
CUTTING NOZZLE 10- 25MM
234807
CUTTING ATTACHMENT 90 DGR
174573
WELDING ATTACHMENT 80L.

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing--cutting/welding-brazing--cutting-torch/welding-attachment-230-l>