

Last updated: 30/03/2023 21:02:28

WELDING ATTACHMENT 80L.

Product group: **170** Product number: **174573**

The welding attachment is used in combination with UCT-500 torch shank for brazing and gas welding.



Product information

The selection of welding attachment with different gas flow rate / capacity will determine the workable material thickness range.

Size* O-A80 for material thickness: 0.5 -1.0 mm

The size indicates consumption of Oxygen in nl/h. Acetylene consumption is approximately 10% lower. Material thickness refers to mild steel.

Specification

General

Technical data

Invent Hazard Material (IMO/EU) classification	NA
--	----

The size indicates consumption of oxygen in nl/h. Acetylene consumption is approximately 10% lower. Material thickness refers to mild steel.

Documents

[SDoC and MD for IHM](#)

Related products

Is accessory to

500001
UCT-500 COMBINATION TORCH COMPACT
500000
UCT-500 COMBINATION TORCH MASTER

Is part of bundle

589861
GASWELDING CABINET COMPLETE

Is frequently bought together with

510000
REGULATOR 510 OX PRESSURE 0-10 BAR

174581
WELDING ATTACHMENT 230 L

174706
CUTTING NOZZLE 10- 25MM

234807
CUTTING ATTACHMENT 90 DGR

175356
CLEANING NEEDLES SET

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing-cutting/welding-brazing-cutting-torch/welding-attachment-80/>