

Last updated: 30/03/2023 21:02:28

## WELDING ATTACHMENT 80L.

Product group: 170 Product number: 174573

The welding attachment is used in combination with UCT-500 torch shank for brazing and gas welding.



### Product information

The selection of welding attachment with different gas flow rate / capacity will determine the workable material thickness range.

Size\* O-A80 for material thickness: 0.5 -1.0 mm

The size indicates consumption of Oxygen in nl/h. Acetylene consumption is approximately 10% lower. Material thickness refers to mild steel.

### Specification

General

Technical data

Invent Hazard Material (IMO/IU) classification	NA
--	----

The size indicates consumption of oxygen in nl/h. Acetylene consumption is approximately 10% lower. Material thickness refers to mild steel.

### Documents

[SDoC and MD for IHM](#)

### Related products

Is accessory to

**500001**  
UCT-500 COMBINATION TORCH COMPACT  
**500000**  
UCT-500 COMBINATION TORCH MASTER

Is part of bundle

**589861**  
GASWELDING CABINET COMPLETE

Is frequently bought together with

**510000**  
REGULATOR 510 OX PRESSURE 0-10 BAR

**174581**  
WELDING ATTACHMENT 230 L

**174706**  
CUTTING NOZZLE 10- 25MM

**234807**  
CUTTING ATTACHMENT 90 DGR

**175356**  
CLEANING NEEDLES SET

This page is printed from

<https://www.wilhelmsen.com/product-catalogue/products/welding/gas-welding-brazing-cutting/welding-brazing-cutting-torch/welding-attachment-80/>