

Last updated: 02/03/2023 06:33:48

Air Hose, Rubber

Rubber reinforced hose for compressed air line use onboard with excellent flexibility, temperature resistance, chemical resistance and good mechanical wear characteristics.

Ideal for use in maritime industry harsh environment.



Product information

Rubber hoses is known for its properties of able to retain its flexibility and at same time being resistant to kinks and abrasions.

Features

- Manufactured to ISO2398/1A standard
- Made of SBR&NBR rubber grades with a synthetic reinforcement
- Supplied in coil of 50 m

Benefits

- Excellent resistance towards mechanical wear
- More flexible than PVC and keeps flexibility even in cold weather
- Conforms to EU Regulations EC 1907 / 2006 regarding no usage of Phthalates (plasticizers) in rubber hose compound

Specification

Technical data

| | |
|---------------------------------|----|
| Burst pressure [bar] | 60 |
| Operating pressure [bar] | 15 |
| Test Pressure [bar] | 40 |

Variants

| Product name | Product number | Burst pressure [bar] | Operating pressure [bar] | Test Pressure [bar] |
|---|----------------------------|----------------------|--------------------------|---------------------|
| <u>AIR HOSE 1", RUBBER (50 MTR. COIL)</u> | 671786 | 6.0Mpa/60BAR | | 4.0Mpa/40Bar |
| <u>AIR HOSE 1/2", RUBBER, 50 METER COIL</u> | 671768 (supersedes 181693) | 6.0 Mpa / 60 BAR | | 4.0 Mpa / 40 BAR |
| <u>AIR HOSE 1/4", RUBBER (50 MTR. COIL)</u> | 671743 | 6.0 Mpa / 60 BAR | | 4.0 Mpa / 40 BAR |
| <u>AIR HOSE 3/4", RUBBER LTH=50MTR</u> | 671776 (supersedes 181693) | 6.0Mpa/60Bar | | 4.0Mpa/40Bar |
| <u>AIR HOSE 3/8", RUBBER (50 MTR. COIL)</u> | 671750 (supersedes 181685) | 6.0 Mpa / 60 BAR | | 4.0 Mpa / 40 BAR |

This page is printed from

<https://www.wilhelmsen.com/zh-hans/product-catalogue/products/air-tools/air-tool-equipment/air-line-equipment/air-hose-rubber>