

Last updated: 12/06/2024 18:11:21

UNITOR HPC STATIONARY 3P

Product group: **435** Product number: **729403**

The Unitor™ HPC Stationary 3P is a flexible pump station that is capable of supplying up to 3 simultaneous operators with pressurized water for high pressure cleaning. Dependant on the amount of operators performing high pressure cleaning on board the vessel, the Unitor™ HPC Stationary detects the line pressure drop and will automatically activate the number of pumps being required.



Product information

This product supersedes product no: **613803**

Three pump stationary cold water unit for medium and heavy cleaning applications in maritime use.

The Unitor Stationary3P model is for heavy cleaning applications with up to 3 users at same time.

Features

- Stainless steel frame and robust cabinet ensuring that pumps and electronics are well protected
- 3 pump system, each pump is equipped with four solid ceramic pistons
- Smart pump control system with touch screen at front panel
- Line pressures can be adjusted
- As water requirement drops, pumps will stop automatically
- Pumps operate on rotation to avoid excessive wear on single pumps
- The lower front panel can be opened for easy access to the pumps
- High level of serviceability, pumps and motors are quickly and easily removed

Benefits

- The pumps are installed on the frame with rubber dampers, and flexible connections to power and water
- Smart control system detects the amount of water required by the relevant number of operators and start the required pumps automatically
- Long life pump for intense applications
- Efficient operation and routine maintenance
- Up to 3 simultaneous operators

Specification

General

Invent Hazard Material (IMO/EU) classification	D-1
--	-----

Dimensions/Weight

Height [mm]	1800
Length [mm]	970
Weight [kg]	349
Width [mm]	1050

Technical data

Amperage [A]	44
Electrical phase	3
Frequency [Hz]	60
Ingress protection	X5
Inlet water temperature [°C]	70 maximum
Operating pressure [bar]	200
Power rating [kW]	27
Voltage [V]	440 V mains supply
Water flow rate [l/min]	63,3 maximum

Documents

[SDoC and MD for IHM](#)

[Instruction manual](#)

Related products

Accessories

718577

NOZZLE 06/25DGR. F/EXTENDABLE LANCE

621821

DRAIN CLEANER 6401268 F/HPC 67, 20M

659151

EXTENDABLE LANCE 5.5MW/OUT NOZZLE

671818

HEAVY DUTY HOSE, BLUE 25M

621938

LONG REACH LANCE

662163

TORNADO LANCE 92CM WITH 05 NOZZLE

546150

DOUBLE LANCE 200CMLONG

623595

TAKE OFF VALVE 6402023 ACID PROOF 316

665158

ERGO 3000 SPRAY GUN

659128

POWERSPEED LANCE WITH 06 NOZZLE

623603

TAKE OFF VALVE 6402024 CHR. PLATED BRASS

545327

CHEM INJECTOR DETACHABLE

586792

HEAVY DUTY HOSE 15 MTR

545335

FOAM INJECTOR DETACHABLE

545434

DOUBLE LANCE 10CMLONG

586784

HEAVY DUTY HOSE 25 MTR

545343

FOAM LANCE 120CMLONG

546044

WASHING BRUSH 235CMLONG

621896

HOSE CART, MOBILE

682070

UNIVERSAL.3000 LANCE 06 NOZZLE

545640

SUCTION HOSE&ROD F/VS300

546036

COUPLING KIT ERGO 3000

718593

NOZZLE 06/0DGR. F/EXTENDABLE LANCE

565861

RUBBER NOZZLE F/VS300

621904

HP HOSE OUTLET (UNITOR STATIONARY 3P, 4P & 6P)

This page is printed from

<https://www.wilhelmsen.com/zh-hans/product-catalogue/products/cleaning-equipment/stationary-high-pressure-systems/stationary-cold-water-cleaners/unitor-hpc-stationary-3p>