

Last updated: 16/02/2024 03:47:23

UNICOOL R-22 12.5 KG REFRIGERANT

Product group: **591** Product number: **905621**

A synthetic HCFC refrigerant that has an Ozone Depleting Potential. The gas is used in a variety of maritime refrigeration applications such as low, medium and high temperatures (-40 to +16° C). Note: the use of R-22 (virgin and reclaimed) is banned in the EU.



Product information

Features

- All refillable cylinders are inspected prior to refilling
- Residue refrigerant recovered to prevent environmental damage
- Content is 100% genuine virgin refrigerant from approved producer
- Conforms to AHRI-700 purity standard

Benefits

- Worldwide compliance
- Assured quality
- Refillable cylinders

Specification

General

Cylinder Type	Refr-12
GWP	1810
Invent Hazard Material (IMO/EU) classification	A-3
ODP	0.049

Physical properties

Colour	Green
--------	-------

Dimensions/Weight

Connection [Size/ Type]	CGA660
Diameter [mm]	229
Gross Weight [kg]	21 approx.
Height [mm]	506
Weight [kg]	12.5 Net

Technical data

ODP = Ozone Depletion Potential

GWP = Global Warming Potential (IPCC Fourth Assessment Report - AR4)

Documents

[SDoC and MD for IHM](#)

Related products

Accessories

597757
CHARGING HOSE SET UCH-72 3X1.8M
544932
REFRIGERANT CYL. VALVE ADAPTOR SET

Is frequently bought together with

905232
NITROGEN N-1030 FILLING
716142
REFRIGERANT LEAK DETECTOR UNIRX-1A
752154
REFRIGERATION HANDY TOOLS CASE
652522
REFRIGERANT RECOVERY PACKAGE F/220V

743466
DUCT AIR TREATMENT 2KG

This page is printed from

<https://www.wilhelmsen.com/zh-hans/product-catalogue/products/gases-refrigerants-and-cylinders/refrigerants/r-22/unicool-r-22-12.5-kg-refrigerant>