

Last updated: 16/02/2024 03:48:21

UNICOOL R-22 57 KG REFRIGERANT

Product group: **591** Product number: **905059**

A synthetic HCFC refrigerant with an Ozone Depleting Potential. The gas is used in a variety of maritime refrigeration applications for low, medium and high temperatures (-40 to +16° C). NOTE: the use of R-22 (virgin and reclaimed) is banned in the EU.



Product information

Features

- All refillable cylinders are inspected prior to refilling
- Residue refrigerant recovered to prevent environmental damage
- Content is 100% genuine refrigerant from approved producer

Benefits

- Worldwide compliance
- Assured quality
- Refillable cylinders

Specification

General

Cylinder Type	Refr-56
GWP	1810
Invent Hazard Material (IMO/EU) classification	A-3
ODP	0.049

Physical properties

Colour	Green
---------------	-------

Dimensions/Weight

Connection [Size/ Type]	CGA660
Diameter [mm]	254
Gross Weight [kg]	86 approx.
Height [mm]	1380
Weight [kg]	57 Net

Documents

[SDoC and MD for IHM](#)

[SDoC and MD for IHM](#)

Related products

Accessories

597757
CHARGING HOSE SET UCH-72 3X1.8M

544932
REFRIGERANT CYL. VALVE ADAPTOR SET

513564
CYLINDER STAND

Is frequently bought together with

905208

NITROGEN N-5030 FILLING

716142

REFRIGERANT LEAK DETECTOR UNIRX-1A

752154

REFRIGERATION HANDY TOOLS CASE

652522

REFRIGERANT RECOVERY PACKAGE F/220V

743466

DUCT AIR TREATMENT 2KG

This page is printed from:

<https://www.wilhelmsen.com/zh-hans/product-catalogue/products/gases-refrigerants-and-cylinders/refrigerants/r-22/unicool-r-22-57-kg-refrigerant>