

Last updated: 16/02/2023 08:38:35



Product group: **718** Product number: **742951**

Span gases are used for calibration and bump testing of gas detection equipment. Currently two types of disposable cylinders are in use depending on the gas mixture: - Minimix 34 is an aluminium disposable cylinder with 34 litres of gas - Minimix 58 is an aluminium disposable cylinder with 58 litres of gas



Product information

Gas Composition:

Methane (CH4) - 2.2% (44% LEL) Oxygen (O2) - 18% Hydrogen Sulfide (H2S) - 15ppm Carbon Monoxide (CO) - 100ppm Nitrogen (N2) - balance

Used with regulator 620013

Features

- Lightweight and disposable cylinder
- Compact size
- Comes standard with CGAC-10 connection
- Each cylinder delivered with a Certificate of Analysis
- Guaranteed and repeatable quality

Benefits

- Safe handling of gas
- Portable and easy to carry around
- Easy stock control
- Single regulator type needed across
- Compliant to vetting inspection requirements

Specification

General

Cylinder Type	Minimix 34
Invent Hazard Material (IMO/EJ) classification	NA

Dimensions/Weight

Connection [Size/ Type]	OGA C-10
Diameter [mm]	76
Height [mm]	289

Technical data

Shelf life [months]	24
Volume (I)	0.9

Documents

SDoC and MD for IHM

Related products

Accessories

620013

REGULATOR F/SCOTTY VI AND 4COMP

Is frequently bought together with

698720

AUTOTREAT - 25 LTR

765018

ENVIROCLEAN 25 LTR

774828

CONDENSATE CONTROL 25 LTR

905034

OXYGEN 0-40 FILLING

571356

ROCOR NB LIQUID 25 LTR

This page is printed from

https://www.wilhelmsen.com/zh-hans/product-catalogue/products/gases-refrigerants-and-cylinders/spangases/disposables/4-mix-100-co-15-h2s-2.2-ch4-18-ox