

Last updated: 15/02/2023 03:39:23

MINIMIX 34 O2 2% IN 98% N2

Product group: **718** Product number: **630057**

Span gases are used for calibration and bump testing of gas detection equipment. Currently two types of disposable cylinders are in use depending on the gas mixture:

- Minimix 34 is an aluminium disposable cylinder with 34 litres of gas
- Minimix 58 is an aluminium disposable cylinder with 58 litres of gas



Product information

Gas Composition:

Oxygen (O2) - 2%

Nitrogen (N2) - balance

Used with Regulator 620013

Features

- Lightweight and disposable cylinder
- Compact size
- Comes standard with CGA C-10 connection
- Each cylinder delivered with a Certificate of Analysis
- Guaranteed and repeatable quality

Benefits

- Safe handling of gas
- Portable and easy to carry around
- Easy stock control
- Single regulator type needed across
- Compliant to vetting inspection requirements

Specification

General

Cylinder Type	Minimix 34
Invent Hazard Material (IMC/EL) classification	NA

Dimensions/Weight

Connection [Size/ Type]	CGA C-10
Diameter [mm]	76
Height [mm]	289

Technical data

Shelf life [months]	36
Volume (l)	0.9

Documents

[SDoC and MD for IHM](#)

[media](#)

Related products

Accessories

620013
 REGULATOR F/SCOTTY V AND 4COMP

This page is printed from

<https://www.wilhelmsen.com/zh-hans/product-catalogue/products/gases-refrigerants-and-cylinders/spangases/disposables/minimix-34-o2-2-in-98-n2>