

Last updated: 02/11/2023 02:01:16

HARDNESS TREATMENT 7208 25 LTR

Product group: **655** Product number: **777706**

NALFLEET™ Hardness Treatment 7208™ is an alkaline liquid phosphate formulation for the prevention of scale in both high and low pressure boilers.



Product information

This product supersedes product no: **571299**

NALFLEET™ Hardness Treatment 7208™ is an Alkaline Liquid phosphate liquid with a Na:PO4 ratio of 2.6:1 that can be used in both coordinated and alkaline phosphate boiler water treatment programmes.

Features

- Liquid product for easy application
- Simple test kit is available

Benefits

- Provides phosphate scale control in both high and low pressure boilers
- May be used as part of a coordinated phosphate programme
- Easy to apply liquid formulation

Specification

General

Invent Hazard Material (IMO/EU) classification	C-9
---	-----

Physical properties

Appearance	Off-White
Density [g/ml]	1.1
Form	Liquid
pH	13.0 to 14.0

Technical data

Not Compatible	Aluminium, Copper, Copper Alloys, Nickel, Neoprene, Polyurethane.
-----------------------	---

Documents

[SDoC and MD for IHM](#)

Directions for use

NALFLEET™ Hardness Treatment 7208 should be fed continuously in order to properly protect the boiler. NALFLEET™ Hardness Treatment 7208 can be fed neat or in any convenient dilution made up in soft water or cooled condensate. NALFLEET™ Hardness Treatment 7208 must not be mixed with oxygen scavengers or condensate system corrosion inhibitors.

Sampling and Testing

NALFLEET™ Hardness Treatment 7208 is normally used in conjunction with NALFLEET™ Alkalinity Control treatment in a conventional alkaline phosphate treatment programme for HP boilers, where independent control of phosphate and alkalinity control is required.

Dosing and Control

The dosage of NALFLEET™ Hardness Treatment 7208 depends on a number of operational factors such as feed-water quality, boiler design and steam rate. Control of NALFLEET™ Hardness Treatment 7208 is by a simple test to give the required level of phosphate (as PO4) in the boiler water. A simple Hardness Treatment test kit is available for this purpose. NOTE: Dependent on water quality, NALFLEET™ Hardness Treatment 7208 dosed at 0.25 liters/ton will increase the phosphate reserve by the order of 10mg/l.

Related products

Accessories

739482
 SPECTRAPAK 311

Is frequently bought together with

680843

COOLTREAT AL 25 LTR

571364

VAPTREAT 25LTR

571356

ROCOR NB LIQUID 25 LTR

735977

MAR-71 BIOCIDES 3X5L NOT IN USA&CAN

638676

EVAPORATOR DEFOAMER 4X5 LTR

698712

OXYGEN SCAVENGER PLUS 25 LTR

777702

CONDENSATE TREATMENT 9-150 25 LTR

777710

NALFLEET 2000 25 LTR

This page is printed from

<https://www.wilhelmsen.com/zh-hans/product-catalogue/products/marine-chemicals/water-treatment-chemicals/boiler-water-treatment/hardness-treatment-7208-25-ltr>