

Last updated: 02/09/2023 00:00:42

# GPO-302N 2.5X350MM 295 PCS 5,2KG

Product group: **095** Product number: **599165**

Electrode for welding of mild steel.



## Product information

This product supersedes product no: **699165**

General purpose organic-rutile coated electrodes for unalloyed steels. Easily weldable in all positions including vertical down. Suitable for bridging large gaps. Excellent for all-purpose repair welding of mild steel.

### Features

- Unitor high density polyethylene packing
- Strikes and re-striking easily
- All positions including vertical down
- Superb arc stability
- Bridge large gaps
- Approved by classification societies for mild steels

### Benefits

- Long storage lifespan
- Superb for tack welding
- Easy to use
- Can do the job even if edge preparation is not up to standard
- In compliance with maritime rules and regulations

## Specification

### General

Invent Hazard Material (IMO/EU) classification	NA
--	----

### Dimensions/Weight

Diameter [mm]	2.5
Weight [kg]	5.2

### Technical data

AWS	E6013
Polarity	AC, DC+/-

### Performance data

Amperage [A]	100
--------------	-----

## Approvals

Contact Customer Service for 3rd party approvals certificates

## Documents

[SDoC and MD for IHM](#)

## Related products

Is frequently bought together with

**699272**  
 LH-314N 3.2X450MM96 PCS 5KG

**699264**  
 LH-314N 2.5X350MM 161 PCS 4.0 KG

**699173**  
 GPO-302N 3.2X350MM 190 PCS 5.4 KG

This page is printed from

<https://www.wilhelmsen.com/zh-hans/product-catalogue/products/welding/arc-welding-consumables-and-storing/coated-stick-electrodes/gpo-302n-2.5x350mm-295-pcs-52kg>