

Last updated: 27/06/2024 01:01:01

WELDING CABLE 35 MM²

Product group: 195 Product number: 175836

Welding cable 35 mm², sold per meter basis



Product information

Welding cables used on board, on deck or in an engine room, are exposed to rough weather, oil and mechanical wear. The welding cable supplied by Unitor has wear, flame and oil-resistant insulation on a polychloroprene rubber basis. It is recognized by its marking at regular intervals with the text "Unitor oil resistant welding cable", size of cable, and the standard for welding cable H01N2-D. H01N2-D means that the cable is produced to an international harmonized standard.

The conductor is built up from 0.2mm diameter tinned copper strands to ensure flexibility.

The cable is available in cross section areas 35mm², 50mm², 70mm², and 90mm²

Features

- Unitor welding cable is oil resistant, flame resistant and wear resistant. The conductor is built up from 0.2mm diameter copper wires to ensure high flexibility
- The Unitor welding cable complies with the harmonised standard H01N2D for flexible welding cable

Specification

General		Dimensions/Weight	
Invent Hazard Material (IMO/EU) classification	NA	Weight [kg]	0.415

Performance data

Amperage [A]	375 Maximum Amperage 35% duty cycle
--------------	-------------------------------------

Documents

[SDoC and MD for IHM](#)

Related products

Is frequently bought together with

632893
CABLE CONNECTOR DIX70 MALE-FEMALE

632786
WELDERS GLOVES. 6 PAIRS

699538
ALUMN-351N 3.2X350MM71 PCS 1.1 KG

699272
LH-314N 3.2X450MMØ6 PCS 5KG

This page is printed from

<https://www.wilhelmsen.com/zh-hans/product-catalogue/products/welding/arc-welding-equipment/cables-and-connectors/welding-cable-35-mm2>