

Last updated: 20/12/2023 02:03:28

CUTTING NOZZLE 153MM LENGTH 25-40MM

Product group: 170 Product number: 183863

The cutting nozzles are specially made for use with UCT-500 gas cutting equipment and with oxy/acetylene gases.

Product information

Nozzles should be selected based on cutting thickness. The basic information is marked directly on the nozzle i.e.:

Nozzle length 153mm Material thickness 25-40 mm Gas consumption OX: 3800nl/h AC: 490nl/h

Features

- Designed for use with oxy/acetylene
- Made from high quality copper alloys
- Machined to precision for correct seating angle to prevent any gas leakages and uniform gas holes

Benefits

- Made with the highest safety in mind for equal pressure torch
- Good cutting performance
- Durable

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Documents

[SDoC and MD for IHM](#)

Related products

Is accessory to

174664
CUTTING ATTACHMENT 75 DGR
234807
CUTTING ATTACHMENT 90 DGR

This page is printed from

<https://www.wilhelmsen.com/zh-hans/product-catalogue/products/welding/gas-welding-brazing-cutting/welding-brazing-cutting-torch/cutting-nozzle-153mm-length-25-40mm>

