

Last updated: 26/06/2023 13:39:38

CUTTING NOZZLE 3- 10MM

Product group: 170 Product number: 174698

The cutting nozzles are specially made for use with UCT-500 gas cutting equipment and with oxy/acetylene gases.



Product information

Nozzles should be selected based on cutting thickness. The basic information is marked directly on the nozzle i.e.:

Nozzle nr 2 Material thickness 3-10 mm Gas OX 1300 nl/h Consumption AC 460 nl/h

Features

- Designed for use with oxy/acetylene
- Made from high quality copper alloys
- Machined to precision for correct seating angle to prevent any gas leakages and uniform gas holes

Benefits

- Made with the highest safety in mind for equal pressure torch
- Good cutting performance
- Durable

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Documents

[SDoC and MD for IHM](#)

[cutting-nozzle](#)

Related products

Is accessory to

500001
UCT-500 COMBINATION TORCH COMPACT

500000
UCT-500 COMBINATION TORCH MASTER

234807
CUTTING ATTACHMENT 90 DGR

174664
CUTTING ATTACHMENT 75 DGR

234815
CUTTING ATTACHMENT 0 DGR

Is part of bundle

589861
GASWELDING CABINET COMPLETE

Is frequently bought together with

905034
OXYGEN O-40 FILLING

905026
ACETYLENE A-40 FILLING

510000
REGULATOR 510 OX PRESSURE 0-10 BAR

699173
GPO-302N 3.2X350MM 190 PCS 5.4 KG

174706
CUTTING NOZZLE 10- 25MM

This page is printed from

<https://www.wilhelmsen.com/zh-hans/product-catalogue/products/welding/gas-welding-brazing-cutting/welding-brazing-cutting-torch/cutting-nozzle-3--10mm>