

Last updated: 30/03/2023 21:02:28

GOUGING NOZZLE

Product group: **170** Product number: **174730**

The gouging nozzles are specially made for use with UCT-500 gas cutting equipment and with oxy/acetylene gases.



Product information

The basic gouging information is marked directly on the nozzle i.e.:

Furrow width 8-11 mm Furrow depth 6-11 mm Gas consumption OX:11500nl/h AC:1750nl/h

Features

- Designed for use with oxy/acetylene
- Made from high quality copper alloys
- Machined to precision for correct seating angle to prevent any gas leakages and uniform gas holes

Benefits

- Made with the highest safety in mind for equal pressure torch
- Good gouging performance
- Durable

Specification

General

Invent Hazard Material (IMO/EU) classification	NA
--	----

Documents

[SDoC and MD for IHM](#)

Related products

Is accessory to

234807
CUTTING ATTACHMENT 90 DGR

174664
CUTTING ATTACHMENT 75 DGR

234815
CUTTING ATTACHMENT 0 DGR

Is frequently bought together with

510000
REGULATOR 510 OX PRESSURE 0-10 BAR

174706
CUTTING NOZZLE 10- 25MM

174698
CUTTING NOZZLE 3- 10MM

632786
WELDERS GLOVES. 6 PAIRS

174714
CUTTING NOZZLE 25- 50MM

This page is printed from

<https://www.wilhelmsen.com/zh-hans/product-catalogue/products/welding/gas-welding-brazing--cutting/welding-brazing--cutting-torch/gouging-nozzle>